



## Mobile Sludge/Slurry Holding Tank

The **GROUNDHOG** range of holding tanks are designed to be towed (empty) by an agricultural type tractor, minimum 90HP. Maximum recommended road speed 20MPH. The single rear axle is equipped with an hydraulic jacking system powered by the towing tractor to enable the tank to be sat flat on the ground when in use, and raised for transport when empty. All valves are lockable as standard ensuring protection from vandalism.

Finish painted with epoxy reinforced paint to customer colour requirements.

### Capacities Available:

4500 Gallon (20.5m<sup>3</sup>)  
6000 Gallon (28m<sup>3</sup>)  
8000 Gallon (36m<sup>3</sup>)  
10000 Gallon (46m<sup>3</sup>)

### Specification

- ◆ Mild steel construction, fully Cross-braced, minimum 5mm plate steel, integral drawbar & chassis.
- ◆ Flotation wheels 16 x 20.
- ◆ Single hydraulic brakes.
- ◆ Fill/discharge/points complete with valves to suit customer requirements.
- ◆ Access ladder to top hatch.
- ◆ Clean out point.
- ◆ Road lighting to current UK regs.
- ◆ Level indication.



**Model PTT 8000**



## **OPTIONS:**

**Filter System:** Easily removed inlet filter system for rag segregation.

**Diesel Tank:** 1100 Litre capacity tank manufactured out of stainless steel or mild steel.  
double skinned to protect against contamination.

**Recirculation:** Independent recirculation inlet complete with valve.

**Tool Box:** Large sealed tool box.

**Repositioned Axle Assembly:** Fitted inboard to aid manoeuvrability.

**Float:** High level float audible warning device to warn of over filling.



**GROUNDHOG Systems** supply a complete range of sludge handling and disposal equipment with systems currently in use throughout the UK and Europe. The range includes pumping equipment and **GROUNDHOG** field distribution systems.